

Pro



Professional
Roofing Systems
to Fit
Modular Structures

Most Frequently Asked Questions

What widths do EPDM rolls come in?
9 feet up to 18 feet.

Are custom lengths available?
Yes, up to 305 feet for .045 and up to 255 feet for .060.

What are the special sizes of Self-Bridging Mate-Line™?
9, 12, & 18-inch widths by 65 feet long or 9 & 12-inch by 100 feet long.

Do you still have to use Lap Sealant when using Self-Bridging Mate-Line™?
Yes, both sides of the mate-line must be caulked.

What if I need a Class A or C rated deck panel?
The Mule-Hide FR Deck Panel is your answer. It reduces the costs associated with traditional five-step deck panel installation by eliminating one step. Class A or C rated single OSB board with proprietary BLAZEGUARD® fire resistant treatment replaces wood & gypsum. Single-side wet application is easy with Mule-Hide Water Base Bonding Adhesive.

What about deck drains and scuppers?
Mule-Hide offers Scuppers and Recessed Drains to fit modular projects.

I want to install white, heat-weldable membrane on some of my lease fleet - how much skill is needed in heat-welding the seams?
Mule-Hide offers in-plant crew training on heat-welding.

What is Cured Cover Tape?
MH Cured Cover Tape is a length of EPDM, factory-bonded to a cured EPDM-based adhesive tape that is highly resistant to the most extreme weather & use situations. Used to cover & seal drip apron or gravel stop. (Apply MH Tape Primer, allow to dry to the touch, apply cover tape & roll thoroughly with a 2" steel roller.)

What is In-Seam Tape - why do I need this special tape?
MH In-Seam Tape is a cured, butyl based, two-sided adhesive tape that bonds on contact. Used to seam EPDM and eliminate applicator inconsistencies & voids. When applied properly (MH Tape Primer must be used) it provides the fastest way to achieve strong, long lasting, watertight field seams.

Can I use Water Base Bonding Adhesive to adhere flashings?
No - since it is applied wet, it is designed for single-side, horizontal applications and will not hold flashings to the wall. You need Solvent Based Bonding Adhesive for adhering membrane and flashings to vertical surfaces.

How long should an Elastomeric Roof Coatings System last?
Acrylics have a life expectancy of 7 to 12 years.

What if I have a heavily rusted metal roof - does this project demand a new metal roof?
Not at all provided the metal is still structurally sound - A-125 Acrylic Metal Roof Primer totally encapsulates existing rust and inhibits the development of new rust. The metal panels must be sound and should be power washed to remove all loose rust. After the A-125 is applied, CRRC® rated & Energy Star® listed A-300 FINISH is then applied.

**Just
in Time**

**Ready to
Install**

**Custom
Sizes**

EPDM
Custom Cuts or
Master Rolls

TPO
Heat-Weldable
White Roofs

DecTec®
Walkable PVC

FR Deck Panel
Class A or C rated

Accessories &
Retrofit Materials

Elastomeric Acrylic
Roof Coatings

www.mulehide.com

**Customer Support
800-786-1492**



TPO, White-On-Black EPDM,
and Ac-300 FINISH are CRRC® rated.



"The name trusted in roofing since 1906"

MULE-HIDE PRODUCTS Co., Inc.

1195 Prince Hall Drive Phone (608) 365-3111 PO Box 1057
Beloit, WI 53511 Fax (608) 365-7852 Beloit, WI 53512-1057



EPDM
Custom Cuts or
Master Rolls

TPO
Heat-Weldable
White Roofs

DecTec®
Walkable PVC

FR Deck Panel
Class A or C rated

Accessories &
Retrofit Materials

Elastomeric Acrylic
Roof Coatings

www.mulehide.com

**Customer Support
800-786-1492**



ESTIMATING TIPS

EPDM Accessories Coverage Rates:

Water Base Bonding Adhesive, 5 gal. or 55 gal. drum, apply 1-sided	100-120 sq. ft. per gal.
Bonding Adhesive (solvent base), 5 gal., apply 2 sided	60 sq. ft. per gal.
Splice Adhesive (black or white), 1 gal., apply 2-sided	50 sq. ft. per gal.
Membrane Cleaner 1 gal.	as needed for cleanup
Black Lap Sealant, 11 oz. tube or 5 gal pail	20 linear ft. per tube
3" In-Seam Tape	25 or 100 linear ft per roll
6" In-Seam Tape	100 linear ft per roll
Tape Primer, 1 gal. or 5 gal.	200 sq. ft. per gal.
All Purpose Bar	10 ft. long pieces
Water Cut-Off Mastic, 11 oz. tube	20 linear ft. per tube
6" RMS (Reinforced Membrane Strip)	100 linear ft per roll
6" RMS with 3" Tape	100 linear ft per roll
6" Uncured Flashing (black or white-on-black)	100 linear ft. per roll
12" Uncured Flashing (black or white-on-black)	100 linear ft. per roll
6" Uncured Flashing Tape	25 or 100 linear ft. per roll
12" Uncured Flashing Tape	50 linear ft. per roll
6" Cured Cover Tape	100 linear ft. per roll
12" Cured Cover Tape	100 linear ft. per roll
Pipe Boots with Clamps 1" to 6" dia.	1 boot per penetration
Pipe Boots w/Tape & Clamps	1 boot per penetration
Pourable Sealer, 1 gal. (Part A & Part B)	212 cubic inch per gal.
Pourable Sealer (Pitch) Pockets-EPDM, 4", 6" or 8" - 1,000 per pail	1 per detail
3" Galvalume Stress Plates (for insulation) 1 every 2 sq.ft.	1,000 per pail
Drill Point Fasteners (for Insulation only), 1 every 2 sq. ft.	1,000 per pail*
Heavy Duty Fasteners (for Membrane/RMS only) 1 every 2 sq. ft.	1,000 per pail*
2" Barbed Seam Plates, (1 per HD Fastenr)	1,000 per pail
(Barbed Seam Plates are used to attach RMS at base of wall, curb, shingle tie-in)	
Pre-cut Corners, 7" x 9" pieces purchased separately	1 per corner
*Sizes 7 and over 500 per pail	

Bridging multi-unit 2,3,4-plex structures (setup & dismantling):

Self-Bridging Mate-Line™ (black or white), many roll sizes & coverage rates*
* See Mule-Hide Modular Price List

TPO Accessories Coverage Rates:

TPO Bonding Adhesive (solvent based, amber), 5 gal.	300 sq. ft. (2-sided)
TPO Tape Primer (regular or Low VOC), 1 gal.	200 sq. ft. per gal.
TPO Weathered Membrane Cleaner, 1 gal.	200 sq. ft. per gal.
TPO Cut-Edge Sealant (white or clear), 8 pints per carton	20 linear ft. per pint
TPO Flashing Strips, reinforced (.045", white or gray), 6" x 100 ft.	50 sq. ft.
TPO Detail Membrane, (.060", white or gray) non-reinforced	
12" x 50 ft. or 24" x 50 ft.	50 sq. ft. or 100 sq. ft.
TPO PS Cover Strip with Tape (white or gray), 6" x 100 ft.	50 sq. ft.
TPO PS Russ Strip with Tape (white), 6" x 100 ft. or 10" x 100 ft.	50 sq. ft. or 83.3 sq. ft.
TPO Premolded Pipe Seal, (white or gray), 8 per carton	3/4" to 8", 1 per penetration
TPO Universal Corners (white or gray) 20 per carton	1 per corner
TPO T-Joint Covers (white or gray), 100 per carton, 4 1/2" circle	1 per T-Joint
TPO Molded Sealant Pockets (white or gray), 5 per carton	6" x 7 1/2" oval
TPO Molded Sealant Pocket Extension Legs (white), 10/carton	10" long
Thermoplastic (1-Part) Pourable Sealer, four 1/2 gal. pouches	122 cubic inches
TPO Coated Metal (white or gray), 10 or 25 per pallet	4" x 10"
TPO Walkway Rolls (white or gray), 34" x 50' each	142 sq. ft.
3" Galvalume Stress Plates (for insulation)	1,000 per pail
Drill Point Fasteners (for Insulation only)	1,000 per pail*
Extra Heavy Duty Fasteners #5 (for Membrane only)	1,000 per pail*
2" Barbed Seam Plates (1 per HD Fastener)	1,000 per pail
All Purpose Bar	10 ft. long pieces
*Size 7" & over - 500 per pail.	

DecTec® Walkable Membrane Accessories Coverage Rates:

Water Base Latex Adhesive, 2.5 gal.	125 sq. ft. per gal.
Contact Adhesive, 5 gal.	50-60 sq. ft. per gal.
DecPatch (floor patch)	10 lb pail
DecScupper	1 per through wall drain
DecDrain	1 per drain
DecCorner (Installed under membrane)	1 per corner
4" Dec Flash	2 per door sill /2 outside corners
	1/2 coverage on 4" post
6" Dec Flash	2 per door sill / 2 outside corners
	1/2 coverage on 6" post
Termination Bar, (1.5" x 10 ft. long pieces)	200 linear ft. per tube
DecClad PVC Drip (2" x 1.5" x 1/2" x 1/2" x 8 ft. long pieces)	250 linear ft. per tube
DecClad PVC Kickout (3" x 1/2" x 1/2" x 8 ft. long pieces)	200 linear ft. per tube

Adhesives Types & Uses:

Water Based Adhesives:

1. Water Base Bonding Adhesive (white) for single-side, wet, horizontal application of EPDM membrane to acceptable high-density wood fiberboard, plywood, Dens-Deck, moisture resistant drywall or an acceptable OSB panel.

Solvent Based Adhesives

1. Splice/Seam Adhesive (black or white) contact adhesive to adhere seams of EPDM and to adhere uncured flashing material to EPDM. TIP - avoid liquid adhesion problems - use our popular in-seam tapes and our new 6" RMS Strip with 3" Tape instead of adhesive!
2. Bonding Adhesive (yellow) to fully adhere EPDM and flashing materials to acceptable insulation boards, metal, wood & other acceptable substrates on both horizontal & vertical surfaces.
3. TPO Bonding Adhesive (amber) to fully adhere TPO membrane and flashing materials to acceptable insulation boards, metal, wood & other acceptable substrates on both horizontal & vertical surfaces.
4. Single Seal Adhesive (black) is a brush or roller grade contact adhesive used as either a bonding adhesive or a splice adhesive. Used primarily on small projects where UL & FM approvals are not required.