




EPDM Roofing System Materials

Coverage Rate
EPDM Membrane
Mate-Lines
Self-Bridging Mate-Line™
Seaming
Metal Vents
Pipe Boots
Pipe Boots w/ Tape
Drains
Walls
Scuppers
Pourable Sealer Pockets
Pre-Cut Corners
Insert Bar

Water Base Bonding Adhesive	100-120 sf per gal (1side)	Yes												
Solvent Adhesive	60 sf per gal (2 side)	Sub								Yes				
Tape Primer	200 sf per gal		Yes	Yes	Yes	War/Alt 2	Yes	Yes			War/Alt 2	War/Alt 2	War/Alt 2	
Splice Adhesive	50 sf per gal (2 side)				Sub	War/Alt 1	Yes							
Lap Caulk	20 lf per tube					Yes	Yes	Yes	Yes			Yes	Yes	
Water Cut Off	10 lf per tube						War	War	Yes	Yes	War			Sub
Mate-Line Tape	65 or 100 lf rolls		Yes								Yes			
Backer Rod	100 lf roll			Yes										
Uncured Flashing	100 lf roll					War/Alt 1					War/Alt 1			
Uncured Flashing Tape	25 or 100 lf rolls					War/Alt 2					War/Alt 2			
RMS or RMS w/tape	100 lf rolls									Yes				
In-Seam Tape	100 lf roll				Yes									
Butyl Tape	50 lf roll					Yes								Yes

Use this easy Reference Chart to answer many of your application-related questions.

Materials ordered for multi-unit setups should be laid out specific to individual modular units.



CUSTOMER SUPPORT
800-786-1492

LEGEND:
Yes = Typical Application
Sub = Substitute Application
War = Required for System Warranty
War/Alt = Alternative to meet System Warranty requirement



MULE-HIDE

Modular Roofing Systems

Modular Product Application Reference Chart

TPO Roofing System Materials

		Coverage Rate	TPO Membrane	TPO Mate-Line	Bridging	Walls	Pipe Boots	Pre-Cut Corners	Drains	Scuppers	Insert Bar	
Water Base Bonding Adhesive	100 sf per gal (1 side)	NO	Heat-Welding Only				Heat-Welding Only					
Solvent Adhesive	40 sf per gal (2 side)	Yes			Yes					Yes		
Water Cut Off	10 lf per tube				Yes	Yes				Yes	Yes	Sub
Membrane for Mate-Line	Standard sheet cuts											
Bridging Material	100 lf roll				Yes							
TPO Flashing	30 lf roll										Yes	
Butyl Tape	50 lf roll											Yes

LEGEND:
 Yes = Typical Application
 Sub = Substitute Application

CUSTOMER SUPPORT
800-786-1492

