



Shur-Gard™ SG-50 Acrylic Coating

SECTION 1

Manufacturer Information		Supplier Information	
Company Name	Pinturas Termicas del Norte	Company Name	Mule-Hide Products Co., Inc.
Address	Aaron Saenz 1902 Col. Santa Maria Monterrey, NL, Mexico 64650	Address	1195 Prince Hall Drive Beloit, Wisconsin, 53511
Phone Number	800-874-6737	Phone Number	800-786-1492

SECTION II Hazardous Ingredients / Identity Information

COMPONENTS – CHEMICAL NAME & COMMON NAMES (HAZARDOUS COMPONENTS 1% OR GREATER; CARCINOGENS 0.1% OR GREATER)		% by weight	OSHA PEL	ACGIH	OTHER LIMITS RECOMMENDED
Styrene-Acrylic co-polymer	No estab.	30-45	10 ppm	.1 ppm	N/A N/A
Fillers, extenders	Mixture	30-45			
1,2 Benzisothiazolin -3-one(biocide)	2634-33-5	0.1-0.3			
Water	7731-18-5	15-30			

SECTION III Physical/Chemical Characteristics

Boiling Point	212°F (100°C)	Weight per gallon	7.8-8.3 lbs
Vapor Pressure (mm Hg.)	17	Melting Point	N/A Liquid
Vapor Density (LB/GAL)	11.0 +/- 0.5	Evaporation Rate (Butyl Acetate=1)	N/A
Solubility in Water	Miscible		
Appearance and Odor	White Soft Paste, Mild Ammonia Odor		

SECTION IV Fire and Explosion Hazard Data

Flash Point (Method Used): N/A	Air % by Volume: N/A
Auto-Ignition: N/A	LEL: N/A
Temperature: N/A	UEL: N/A
EXTINGUISHING MEDIA	
N/A	
UNUSUAL FIRE AND EXPLOSION HAZARDS	
N/A	

SECTION V Reactivity Data	
STABILITY:	Stable
Incompatibility (Materials to Avoid):	N/A
Hazardous Decomposition Products:	N/A
HAZARDOUS POLYMERIZATION:	Will Not Occur

SECTION VI Health Hazard Data
PRIMARY ROUTES OF ENTRY: X Inhalation X Skin Absorption X Eyes X Ingestion
HEALTH HAZARDS
May cause minor irritation to skin, eyes or throat.
EYE CONTACT
Flush with large amounts of water, lifting upper and lower lids occasionally. Get medical attention.
SKIN CONTACT
Remove contaminated clothes and wash with waterless handcleaner or soap and water.
INHALATION
Breathe fresh air.
INGESTION
Consult a physician.

SECTION VII Precautions for Safe Handling and Use
STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED
Keep people away. Remove with inert absorbent. Avoid breathing vapors. Ventilate confined spaces. Floor may be slippery. Use caution to avoid falling.
WASTE DISPOSAL METHODS
Assure conformity with applicable disposal regulations. Incinerate in approved facility, do not incinerate in closed container.
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE
Keep containers closed when not in use. Do not store above 120°F (48°C) or below 40°F (4°C).
OTHER PRECAUTIONS AND/OR SPECIAL HAZARDS
Avoid breathing vapors. Avoid prolonged or repeated contact with skin. Remove contaminated clothing and launder before reuse. Remove contaminated shoes and thoroughly dry before reuse. Wash skin thoroughly with soap and water after contact. Do not allow to freeze, protect containers from rupture.

SECTION VIII Control Measures	
RESPIRATORY PROTECTION (SPECIFY TYPE):	N/A
PROTECTIVE GLOVES:	Use chemical resistant gloves if needed to avoid repeated or prolonged skin contact
EYE PROTECTION:	Use OSHA approved glasses, splash goggles or face shield when eye contact may occur.
VENTILATION TO BE USED:	Maintain positive flow of fresh air.
OTHER PROTECTIVE CLOTHING AND EQUIPMENT:	Use other clothing to avoid repeated or prolonged skin contact.
HYGIENIC WORK PRACTICES:	Practice good work hygiene.

SECTION IX Transportation Data
For ground and water domestic transport: Not USDOT regulated.
Not classified as a hazardous material under HM 181.

SECTION X - Other Information

Prepared By: R & D

Issue Date: 04/14/09

Revision Notes: This revision is due to change in Manufacturer/Supplier information.