

PRODUCT DATA SHEET

MULE-HIDE PVC MEMBRANE CLEANER

PRODUCT DESCRIPTION

Mule-Hide PVC Membrane Cleaner is a clear liquid solvent.

BASIC USES

Mule-Hide PVC Membrane Cleaner is used to clean areas on the PVC membrane that has been exposed to weather prior to welding new material. This cleaner helps to loosen and remove dirt and other contaminants from the surface of the PVC membranes and leaves a suitable surface for welding.

SPECIFICATIONS

Color:	Clear
Flash Point:	-4°F (-20°F)
Solubility in Water:	Complete
Boiling Point:	133°F (56.1°C)

PACKAGING AND STORAGE

Mule-Hide PVC Membrane Cleaner comes in a 5 gallon (18.9L) closed top pail. Store in a cool, dry, well ventilated area. Keep away from heat, sparks and open flame.

COVERAGE RATE

Coverage rate and usage is dependent upon the age of the membrane and the amount of dirt and debris on the membrane surface. Typical application may be up to 400 square feet (121 m²) per gallon.

APPLICATION

1. Remove as much loose material as possible from the membrane surface by brooming or wiping the area with a dry rag. Extreme conditions of accumulated dirt may require detergent and water cleaning (rinse area thoroughly with CLEAN water and allow to dry).
2. Saturate a clean natural fiber (cotton) rag with PVC Membrane Cleaner. Scrub the area in a circular motion. Continue to clean the area, changing wipes or rags frequently, until the surface is a consistent white color with no streaking. Additional cleaning is required at factory seams (scrub parallel to the seam). Allow to dry.
3. Perform the heat welded splice according to product instructions and/or roofing system specification.
4. For aged material use an abrasive pad and PVC Membrane Cleaner. Scrub the area to be welded. (the cleaner will become white with membrane residue during this step of the procedure).
5. Clean all residue from the area to be welded with a dry natural fiber (cotton) rag. Wipe area a second time with a clean rag dampened with the PVC Membrane Cleaner to ensure removal of any remaining residue. Allow area to dry.
6. Weld the cleaned material together with an appropriate hot air welder.

MULE-HIDE PRODUCTS CO., INC.

P.O. Box 1057, Beloit, WI 53512-1057 • 608/365-3111 • Fax: 608/365-7852 • www.mulehide.com

MULE-HIDE PVC MEMBRANE CLEANER (Page 2)

PRECAUTIONS

Read Material Safety Data Sheet prior to using Mule-Hide PVC Membrane Cleaner.

- 1. WARNING! HARMFUL IF SWALLOWED. FLAMMABLE LIQUID. MAY BE IRRITATING TO SKIN AND EYES.**
2. Wash thoroughly after handling. Avoid contact with eyes, skin and clothing. Use of solvent resistant gloves and safety glasses recommended. Keep away from heat, sparks, motors and open flame. **DO NOT SMOKE WHILE USING.** Keep lid closed when not in use. **Keep out of the reach of children.**
3. If swallowed, **DO NOT INDUCE VOMITING.** Call physician immediately. In case of eye contact, flush with water for at least 15 minutes. In case of skin contact, wash with soap and water. If irritation develops, call physician.
4. In case of fire, handle as a solvent or gasoline fire. Use dry chemical, carbon dioxide or foam fire extinguishers. Water fog or spray may be used to smother the fire and cool containers. Do not use a solid stream of water to fight fire because it can scatter and spread the fire.

TECHNICAL SERVICES

Contact Mule-Hide Products Co., Inc. at 608/365-3111 for technical service information.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not make nor does it authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Mule-Hide's physical properties. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury of person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the complaint or failure before repairs are made.

MULE-HIDE PRODUCTS CO., INC.

P.O. Box 1057, Beloit, WI 53512-1057 • 608/365-3111 • Fax: 608/365-7852 • www.mulehide.com