

MULE-HIDE PVC CUT-EDGE SEALANT

PRODUCT DESCRIPTION

Mule-Hide PVC Cut-Edge Sealant is a free flowing polymeric material designed for use at the cut edge (exposed scrim) of Mule-Hide PVC reinforced Membrane seams after the membrane has been welded to itself or to Mule-Hide PVC Coated Metal.

BASIC USES

Mule-Hide PVC-Edge Sealant is required to seal all cut edges of membrane seams where the reinforcing scrim is exposed to weather.

SPECIFICATIONS

| | |
|------------------------|---|
| Base: | PVC |
| Colors: | Translucent |
| Coverage Rate: | Approximately 80 linear feet of 1/8" bead per 16 oz. bottle*. |
| Solids: | 18% |
| Viscosity: | 740 cps |
| Flash Point: | 1°F (-17°C) |
| Net weight per gallon: | 7.95lbs.(3.6kg) |
| Resistance to: | |
| Ozone | Excellent |
| UV | Excellent |
| Water | Excellent |
| VOC: | 750 GPL |
| Shelf Life: | 1 year |

*Coverage rate will vary with environmental conditions.

PACKAGING AND STORAGE

Mule-Hide PVC Cut-Edge Sealant is available in 16 oz. bottles packaged 12 bottles per carton. PVC Cut-Edge Sealant must be stored in a dry area protected from weather and extreme temperatures until just prior to use. Do not allow the sealant to freeze. Close container tightly after each use.

INSTALLATION INSTRUCTIONS

Apply Mule-Hide PVC Cut-Edge Sealant to clean, dry membrane surfaces only. **Shake bottle thoroughly prior to each use.** Using the squeeze bottle, run a 1/8" (3mm) bead of sealant along the exposed edge of the seam to form a smooth fillet. Do not apply PVC Cut-Edge Sealant on vertical surfaces. The Cut-Edge Sealant should be dry to touch in about 2 hours and fully cured in 24 hours depending on weather conditions and thickness of product.

PRECAUTIONS

Read Material Safety Data Sheet prior to using Mule-Hide PVC Edge Sealant. Adequate ventilation must be provided. Keep away from heat, sparks and open flame.

1. PVC Cut-Edge Sealant is **EXTREMELY FLAMMABLE** -- It contains solvents that are dangerous fire and explosion hazards when exposed to heat, flame or sparks. Do not smoke while applying. Do not use in a confined or unventilated area. Vapors are heavier than air and may travel along the ground to a distant ignition source and flashback.

MULE-HIDE PRODUCTS CO., INC.

P.O. Box 1057, Beloit, WI 53512-1057 • 608/365-3111 • Fax: 608/365-7852 • www.mulehide.com

MULE-HIDE PVC CUT-EDGE SEALANT (Page 2)

2. Avoid breathing vapors. Keep container closed when not in use. Use with adequate ventilation. If inhaled, remove to fresh air. If not breathing, perform artificial respiration. If breathing is difficult, give oxygen. Call a physician immediately.
3. If swallowed, **DO NOT INDUCE VOMITING**. Call a physician immediately.
4. Avoid contact with eyes. Safety glasses or goggles are recommended. If splashed in eyes, immediately flush eyes with plenty of water for at least 15 minutes. Contact a physician immediately.
5. Avoid contact with skin. Wash thoroughly after handling. In case of contact with skin, thoroughly wash affected area with soap and water.
6. Job site storage temperatures in excess of 90°F (32°C) may affect product shelf life. Should the Cut-Edge Sealant be stored at temperatures below 60°F (15°C), restore to room temperature prior to use.
7. **KEEP OUT OF THE REACH OF CHILDREN.**

TECHNICAL SERVICES

Contact Mule-Hide Products Co., Inc. at 608/365-3111 for technical service information.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not make nor does it authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Mule-Hide's physical properties. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury of person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the complaint or failure before repairs are made.

MULE-HIDE PRODUCTS CO., INC.

P.O. Box 1057, Beloit, WI 53512-1057 • 608/365-3111 • Fax: 608/365-7852 • www.mulehide.com