

MULE-HIDE PVC COATED METAL

PRODUCT DESCRIPTION

Mule-Hide PVC Coated Metal is a laminate of Mule-Hide PVC non-reinforced flashing and galvanized steel. It is used by the contractor to fabricate metal flashings and edge details. PVC membrane may be welded directly to the coated metal.

SPECIFICATIONS

Color: White
Weight: 1.1lb/sf (5.4 kg/m²)
Size: 4' x 10' (1.2m x 3.0m)
Flashing Thickness: 0.035 inches (0.9mm) nominal
Steel Thickness: 0.024 inches (0.6mm) nominal
Steel Type: Hot Dipped Galvanized Steel - G90

PACKAGING

Packaging is 30 sheets per skid. Weight per skid is approximately 1560 lbs. for 10' lengths.

STORAGE

Mule-Hide PVC Coated Metal must be kept dry and clean prior to installation. The PVC Coated Metal must be stored flat, not on end, protected from warping, bending or contamination.

INSTALLATION

Refer to the Mule-Hide PVC Specifications and Details for instructions.

PRECAUTIONS

Do not install Mule-Hide PVC Coated Metal in a manner where the membrane side would be in direct contact with asphalt or coal tar pitch.

TECHNICAL SERVICE

Contact Mule-Hide Products Company at 608/365-3111 for technical service information.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not make nor does it authorize anyone to make any warranty of merchantability or fitness for any purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Mule-Hide's physical properties. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury of person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the complaint or failure before repairs are made.

MULE-HIDE PRODUCTS CO., INC.

P.O. Box 1057, Beloit, WI 53512-1057 • 608/365-3111 • Fax: 608/365-7852 • www.mulehide.com