

A-151 EPDM ReSurface Agent™

DESCRIPTION

Mule-Hide A-151 EPDM ReSurface Agent™ ("A-151") is a ready-to-use, surface preparation agent that is excellent at removing dirt, oil, and grease from EPDM roof decks. A-151 promotes a "lock and key mechanism" which dramatically improves the adhesion of Mule-Hide A-300 FINISH to EPDM (old or new). A-300, the partner product to A-151, is ENERGY STAR® compliant.

USES

Mule-Hide A-151 is designed to prepare the surface of EPDM prior to the application of Mule-Hide A-300 FINISH.

COLOR

The color is clear to pink.

PACKAGING

Packaging is standard in 5 gallon pails.

APPLICATION EQUIPMENT

A 2-3 gallon agricultural type sprayer or a commercial air-less sprayer is needed. A commercial power washer with a minimum 2000 psi will be needed to remove or rinse the A-151 from the roof surface.

APPLICATION

Apply A-151 full strength using an agricultural sprayer or any air-less spray equipment. Adjust the spray nozzle to a uniform spray pattern. A continuous spray pattern with a 3 to 4 foot arc works the best. Allow the A-151 EPDM ReSurface Agent™ to stand for a minimum of 5 minutes. Power wash using a commercial power-washer, with a minimum pressure of 2000 psi. and a spray (fan) tip of not less than .040 inches. Hold the spray tip approximately 12 inches from the roof membrane. **Use care not to damage the EPDM membrane or seams by holding the spray tip too close to the membrane.** Begin cleaning at the highest point of the roof. Use a constant overlapping pattern and work down the roof. When properly cleaned, the EPDM surface will become jet-black. If streaking is apparent, repeat the rinse step until the EPDM is totally clean and black. Allow the roof to dry completely when cleaned and before applying Mule-Hide A-300 FINISH. Smaller roofs can be cleaned all at once. For larger projects section off the roof to complete the cleaning process and finish coating. Always take care so as not to damage the roofing membrane or any of its components.

COVERAGE RATE

One (1) gallon covers 500 square feet.

CLEAN UP

Upon completion of the application, tools, hoses and equipment must be flushed and cleaned immediately with water.

TECHNICAL SERVICE

Contact Mule-Hide Products Company at 800/786-1492 for technical service information.

PRIOR TO USE OF THIS MATERIAL, READ ALL APPROPRIATE MATERIAL SAFETY DATA SHEETS AND WARNINGS.

Mule-Hide Products Co., Inc.

P.O. Box 1057
Beloit, WI 53512-1057
800-786-1492

Product Data Sheet

Form: PDS A-151
Date: 01/02/2002
Page: 2

HEALTH AND SAFETY PRECAUTIONS

WEAR CHEMICAL SPLASH GOGGLES. Mule-Hide A-151 EPDM ReSurface Agent™ has a high pH (11.0 – 12.0). The product as supplied is described as a hazardous product under OSHA's hazard communication standards. As with all chemicals, use caution and good industrial hygiene when handling and disposing of empty containers. Ensure that there is proper drainage for the run-off water from the roof. The rinse water generated from cleaning should never be discharged directly into any open body of water. The diluted A-151 rinse water can be safely discharged onto the ground surface. If in doubt, always contact the local authorities prior to discharging to the soil surface.

NOTE: Do not discharge into any open body of water.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not make nor does it authorize anyone to make any warranty of merchantability or fitness for any purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Mule-Hide's physical properties. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury of person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the complaint or failure before repairs are made.