

PRODUCT DATA SHEET

MULE-HIDE ALL PURPOSE SEALANT (WHITE)

PRODUCT DESCRIPTION

Mule-Hide's All Purpose Sealant (White) is a one-part, elastomeric, multi-use sealant.

BASIC USES

Mule-Hide All Purpose Sealant (White) can be used for sealing EPDM, TPO, and Hypalon field seams, wherever a white sealant is required. All Purpose Sealant can also be used as a flashing and termination sealant around vents, pipes, curbs, wall flashings and at the top of termination bars. **DO NOT USE ON PVC MEMBRANES.** Refer to the Mule-Hide EPDM Manual for appropriate use of All Purpose Sealant when seams and flashings are completed with Mule-Hide Tape Products.

PRODUCT BENEFITS

- Excellent resistance to heat and moisture
- Good resistance to ozone and UV light
- Adheres well to EPDM, TPO, Hypalon, metal, wood, and concrete
- Easily extruded throughout application temperature range

SPECIFICATIONS

Typical Liquid Properties* at 77°F

Base Polymer	Butyl
Color	White
Solids, %	64%
Solvents	Toluene
Specific Gravity	1.036
Pounds per Gallon	9.21
Flash Point	42°F(5.6°C)

*Typical Values: Based on material tested in our laboratories but variable from sample to sample. Typical values should not be construed as a guaranteed analysis of any specific lot or as specification items.

Coverage at 77°F, (theoretical)	200 Linear ft/gal - 20 Linear ft/cartridge
Application Temperature	20°F to 90°F
Service Temperature	-60°F to 180°F

PACKAGING AND STORAGE

12 (10.3 oz) Cartridges per carton

DOT Label Required: Flammable Liquid

Mule-Hide All Purpose Sealant should be stored in a closed container between 60°F and 80°F for no longer than one year. Rotate stock.

INSTALLATION INSTRUCTIONS

Remove all dust or other foreign material surfaces to be bonded. Clean membrane thoroughly, with Mule-Hide Seam Cleaner prior to application of the All Purpose Sealant. Bring sealant to room temperature prior to use at temperatures below 70°F. Do not apply at temperatures below 20°F. Seams and flashings should be completed at least 2 hours prior to application of All Purpose Sealant. Apply a 1/4" to 3/8" bead of sealant along the exposed membrane edge. Do NOT trowel.

Form # PDS-E-19
Date 01/01/2007

MULE-HIDE PRODUCTS CO., INC.

P.O. Box 1057, Beloit, WI 53512-1057 • 608/365-3111 • Fax: 608/365-7852

PRODUCT DATA SHEET

MULE-HIDE ALL PURPOSE SEALANT (WHITE)

CLEANER

Toluene, Xylene or Trichloroethene may be used.

PRECAUTIONS

Mule-Hide All Purpose Sealant contains ingredients, which could be harmful if mishandled. Contact with skin and eyes should be avoided and necessary protective equipment and clothing should be worn.

Mule-Hide maintains Material Safety Data Sheets on all of its products. Material Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. Our material Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Mule-Hide products in your facilities.

TECHNICAL SERVICES

Contact Mule-Hide Products Co., Inc. at 608/365-3111 for additional information.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not make nor does it authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Mule-Hide's physical properties. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury of person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the complaint or failure before repairs are made.

Form # PDS-E-19
Date 01/01/2007

MULE-HIDE PRODUCTS CO., INC.

P.O. Box 1057, Beloit, WI 53512-1057 • 608/365-3111 • Fax: 608/365-7852

PRODUCT DATA SHEET

MULE-HIDE PRODUCTS CO., INC.

P.O. Box 1057, Beloit, WI 53512-1057 • 608/365-3111 • Fax: 608/365-7852