

MULE-HIDE ALL PURPOSE SINGLE SEAL ADHESIVE

PRODUCT DESCRIPTION

Mule-Hide All Purpose Single Seal Adhesive is a black synthetic rubber based product designed specifically as a premium grade brush and roller applied contact adhesive for bonding EPDM membrane materials in single ply roofing systems. The resin reinforced rubber in this adhesive produces strong bonds that are resistant to moisture, oil, and grease. Maximum physical and chemical properties are achieved after 2-3 days from time of application.

BASIC USES

Mule-Hide All Purpose Single Seal Adhesive may be used as either a splice or bonding adhesive. This product eliminates the need for two products at the job site. All Purpose Single Seal Adhesive bonds EPDM to metal, wood, concrete, and approved insulation boards.

SPECIFICATIONS

Base:	Polychlorophrene
Viscosity:	2800-3200 cps
Specific Gravity:	0.86
Color:	Black
Odor:	Mild
Bonding Range:	Approximately 2 hours
Coverage:	Approximately 60 sf/gal (2 side application)

Typical Values: Based on material tested in our laboratories but variable from sample to sample. Typical values should not be construed as a guaranteed analysis of any specific lot or as specification items.

PACKAGING AND STORAGE

DOT Label Required: Flammable Liquid

Materials should be stored in a cool dry area away from heat, sparks and open flame.

INSTALLATION INSTRUCTIONS

Bonding Adhesive - Materials to be bonded should be clean, dry and free of contaminates. Stir the adhesive thoroughly before use. Using a standard solvent resistant roller, apply the adhesive to the underside of the membrane, and to the roof deck, at a rate of 60 square feet per gallon on two sided application. Allow to dry approximately 15 to 30 minutes before assembly. Roll membrane onto the coated underlayment. After mating, broom the membrane using adequate pressure to ensure positive contact between the membrane and the underlayment.

Splice Adhesive - Position the membrane to overlap the distance recommended for the application. Clean seams of roofing membrane by using the Mule-Hide Seam Cleaner. Scrub Mule-Hide Seam Cleaner on splice area and allow to dry. Apply a uniform coat of adhesive to both primed surfaces with a clean brush or roller using consistent strokes parallel to the direction of the splice. Allow surfaces to dry approximately 15 to 30 minutes (environmental conditions may affect drying time).

Form # PDS-E-13
Date 01/01/2007

MULE-HIDE PRODUCTS CO., INC.

P.O. Box 1057, Beloit, WI 53512-1057 • 608/365-3111 • Fax: 608/365-7852

MULE-HIDE ALL PURPOSE SINGLE SEAL ADHESIVE

INSTALLATION INSTRUCTIONS (cont'd)

Assemble seams together. Immediately roll the splice with a 2" wide steel roller with adequate pressure to ensure that intimate contact is made. After splice has been assembled, apply a bead of lap sealant along the exposed edge of the splice.

Note: Mule-Hide Tape Primer or Seam Cleaner must be used when the Mule-Hide All Purpose Single Seal is used as a splice adhesive!

Estimated Coverage Rates*

<u>Splice Width</u>	<u>Coverage (Linear Feet/Gallon)</u>
4"	130-150 lf.
6"	90-110 lf.

*(5 mils thick, dry, both sides)

PRECAUTIONS

Mule-Hide All Purpose Single Seal Adhesive contains ingredients which could be harmful if mishandled. Contact with skin and eyes should be avoided and necessary protective equipment and clothing should be worn.

Mule-Hide Products Co., Inc . maintains Material Safety Data Sheets on all of its products. Material Safety Data Sheets contain health and safety information for your development of appropriate products handling procedures to protect your employees and customers. Our Material Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Mule-Hide products in your facility.

TECHNICAL SERVICES

Contact Mule-Hide Products Co., Inc. at 608/365-3111 for additional information.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not make nor does it authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Mule-Hide's physical properties. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury of person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the complaint or failure before repairs are made.

PRODUCT DATA SHEET

MULE-HIDE PRODUCTS CO., INC.

P.O. Box 1057, Beloit, WI 53512-1057 • 608/365-3111 • Fax: 608/365-7852