

**MULE-HIDE TPO CUT-EDGE SEALANT**

**PRODUCT DESCRIPTION**

Mule-Hide TPO Cut-Edge Sealant is a thermoplastic compound designed for use at the edge of cut Mule-Hide TPO-c membrane seams after the membrane has been welded to itself or to Mule-Hide TPO Coated Metal.

**BASIC USES**

Mule-Hide TPO Cut-Edge Sealant is required to seal all cut edges of membrane (seams and flashing) where the reinforcing scrim is exposed to weather.

**SPECIFICATIONS**

Colors: Clear  
Coverage Rate: Approximately 225'-275' (68-83m) linear feet of 1/8" (3 mm) bead.  
Coverage rate will vary with environmental conditions.

**PACKAGING AND STORAGE**

Mule-Hide TPO Cut-Edge Sealant is available in 16 oz. bottles packaged 8 per carton. Job site storage temperatures in excess of 90°F (32°C) may affect product shelf life. Should the TPO Cut-Edge Sealant be stored at temperatures below 60°F (15°C), restore to room temperature prior to use. Do not allow to freeze. **KEEP OUT OF REACH OF CHILDREN.**

**INSTALLATION INSTRUCTIONS**

TPO Cut-Edge Sealant has a tendency to settle. **SHAKE WELL PRIOR TO EACH USE.** Apply Mule-Hide TPO Cut-Edge Sealant to clean, dry membrane surfaces only. Using a squeeze bottle, run a bead of sealant along the exposed edge of the seam to form a smooth fillet. Do not apply TPO Cut-Edge Sealant on vertical surfaces. Sealant should be tack-free in 2 hours and fully cured in 24 hours depending on weather conditions and application thickness.

**PRECAUTIONS**

Read Material Safety Data Sheet prior to using the Mule-Hide TPO Cut-Edge Sealant. Adequate ventilation must be provided. Safety glasses or goggles are recommended. Avoid contact with skin. Keep away from heat, sparks and open flame.

**TECHNICAL SERVICES**

Contact Mule-Hide Products Co., Inc. at 608/365-3111 for technical service information.

**DISCLAIMER**

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not make nor does it authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Mule-Hide's physical properties. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury of person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the complaint or failure before repairs are made.

Form # PDS-TPO-06  
Date 01/01/2006

**MULE-HIDE PRODUCTS CO., INC.**

P.O. Box 1057, Beloit, WI 53512-1057 • 608/365-3111 • Fax: 608/365-7852