

PRODUCT DATA SHEET

Liqui-Thix®

DESCRIPTION

Mule-Hide Liqui-Thix® is a unique blend of acrylic copolymers designed to convert standard A-300 FINISH or A-400-W MASONRY WALL COATING into a thick, flashing /caulking grade sealant. Because Liqui-Thix® is an acrylic emulsion as opposed to a fibrated or powdered thickener, the resultant flashing grade product has excellent physical properties and a smooth, buttery consistency. Liqui-Thix® can be used on the job site to permanently transform the acrylic coating into a flashing grade in seconds.

TYPICAL PHYSICAL PROPERTIES

| | |
|---------------------------|------------------|
| Weight / Gallon | 8.6 +/- 0.2 lbs. |
| Solids (% by wt.) | 16.0 +/- 0.5 |
| Viscosity - cps | 100 max. |
| pH | 3.7 +/- 0.3 |
| Storage Temperature Range | 40°F to 100°F |

COLORS

Liqui-Thix® is a clear tint, which should not change the color of the acrylic coating. However, Mule-Hide does not guarantee color match and recommends spot-checking to confirm a satisfactory color match.

PACKAGING

Packaging is standard in 32 ounce wide mouthed plastic jugs.

INSTRUCTIONS

Shake well before using. One 32-ounce bottle of Liqui-Thix® will convert one five-gallon pail of Mule-Hide A-300 or A-400-W into a thick, flashing grade sealant. Thoroughly mix* one five gallon pail of A-300 Finish or A-400-W Masonry Wall Coating. **While mixing the A-300 or A-400-W**, pour in one standard container of Liqui-Thix®. Continue mixing for approximately one minute or until the thickened product has consistency throughout.

A 400 r.p.m. 1/2" electric drill with a rectangular plaster paddle is required.

CLEAN UP

Clean up can be made using a mild detergent and water solution while coating is still wet; Mule-Hide 115 CLEANER is recommended. Make sure all materials; debris, containers, etc. are removed from work area and properly disposed.

TECHNICAL SERVICE

Contact Mule-Hide Products Company at 800/786-1492 for technical service information.

Prior to use of this material, read all appropriate Material Safety Data Sheets and warnings.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not make nor does it authorize anyone to make any warranty of merchantability or fitness for any purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Mule-Hide's physical properties. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury of person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the complaint or failure before repairs are made.

Form # PDS Liqui-Thix
Date 08/2004

MULE-HIDE PRODUCTS CO., INC.

P.O. Box 1057, Beloit, WI 53512-1057 • 608/365-3111 • Fax: 608/365-7852