

MULE-HIDE POURABLE SEALER

PRODUCT DESCRIPTION

Mule-Hide Pourable Sealer is a two component, solvent free, polyurethane based product compatible with Mule-Hide's various EPDM systems. Mule-Hide Pourable Sealer was designed to provide a flexible, yet long lasting seal around hard to flash penetrations through the roof deck.

BASIC USES

Mule-Hide's Pourable Sealer is used primarily as a filler for sealing pitch pans. This product may also be used to provide a permanent tie-in between EPDM membranes and a built-up roof system.

SPECIFICATIONS

Color	Black
Tensile Strength	100 psi
Flash Point	Part A = 490°F, Part B = 220°F
Hardness	37
Low Temperature, Brittleness	-50°F
Permeability	.105 Perm Inch
Solids Content	100%
Specific Gravity	1.19
Elongation	180%

COVERAGE

One gallon of Pourable Sealer contains 231 cubic inches for filling Pitch pans. Due to waste and crowning, 200 cubic inches should be used as a guideline to determine gallons required. One gallon of Pourable Sealer will cover approximately 19 linear feet of cold tie-in 6 inches wide on a smooth surface. Coverage will vary according to surface roughness and thickness of application.

PACKAGING AND STORAGE

Each carton contains: 2 - 1 Gallon Cans (Part A)
2 - 1 Pint Cans (Part B)

Shelf life is established at one year. Shelf life is based on storage in original, unopened or undamaged containers at temperatures ranging from 60°F to 80°F. Should the Pourable Sealer be exposed to lower temperatures, restore to room temperature prior to use.

MIXING INSTRUCTIONS

Thoroughly mix the Part B (1 pint can) and pour contents into Part A (1 gallon can). Thoroughly stir components together using a variable speed drill and mixing blade for a minimum of 5 minutes. Be sure to scrape the sides of the can to ensure uniform mixing. Note: Part B (1 pint can) may be pressurized - open container slowly.

Note: When mixed, Pourable Sealer has a pot life of approximately 30 minutes.

MULE-HIDE POURABLE SEALER

INSTALLATION INSTRUCTIONS

A. Pitch Pans

Fit the EPDM membrane as tightly as possible around the penetrating object and seal as necessary to prevent loss of filler. Install and flash pitch pans in accordance with the appropriate details. Minimum Pourable Sealer depth required is 2 inches. Minimum distance from object to the side of the pans is 1 inch. Clean all mating surfaces with Mule-hide Seam Cleaner and fill pan with properly mixed Pourable Sealer in sufficient quantity to crown the top surface to prevent ponding water.

B. Tie-in to Built-Up Roof Surfaces

Scrape and clean the built-up surface to remove all gravel, dirt and moisture in the tie-in area to ensure the surface is smooth, clean and dry. When properly mixed, apply the Pourable Sealer as specified and embed the Uncured EPDM Flashing as shown in the detail section of the Mule-Hide Manual.

PRECAUTIONS

Mule-Hide Pourable Sealer contains ingredients that could be harmful if mishandled. Contact with skin and eyes should be avoided and necessary protective equipment and clothing should be worn.

Mule-Hide maintains Material Safety Data Sheets on all of its products. Material Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. Mule-Hide's Material Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Mule-Hide products in your facilities.

TECHNICAL SERVICES

Contact Mule-Hide Products Co., Inc. at 608/365-3111 for additional information.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not make nor does it authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Mule-Hide's physical properties. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury of person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the complaint or failure before repairs are made.

Form # PDS-E-21
Date 01/01/2007

MULE-HIDE PRODUCTS CO., INC.

P.O. Box 1057, Beloit, WI 53512-1057 • 608/365-3111 • Fax: 608/365-7852