

MULE-HIDE PRE-CUT INSIDE/OUTSIDE CORNERS

PRODUCT DESCRIPTION

Mule-Hide Pre-Cut Inside/Outside Corners consist of .060 inch (1.5mm) thick uncured EPDM flashing material laminated to cured butyl rubber tape and rolled onto a poly release liner providing .090 mils (2.25mm) of total thickness.

BASIC USES

Mule-Hide's Pre-Cut Corners can be installed as either an inside or an outside corner.

SPECIFICATIONS

Sizes: 7" x 9" (175mm x 230mm)
Packaging: 20 per carton
Weight: 5 lbs. per carton (2.25Kg)
Color: Black
Shelf Life: Six (6) months when stored between 60°F - 80°F (15°C - 26°C)

PACKAGING AND STORAGE

Keep the material clean. Materials should be stored in a cool dry location.

INSTALLATION INSTRUCTIONS

Inside Corners: Apply a uniform coat of Tape Primer to the curb flashing and onto the deck membrane where the inside corner is to be installed. Remove the blue poly film, then fold the corner lengthwise and proceed to fold again quarterly. Remove half of the clear release liner. Place a quarter section onto the deck with long folded side facing the wall. Remove the remaining release paper. Press firmly and proceed with the second quarter going up the vertical wall pressing firmly into the corner. Next, form a pig ear with the excess material. Apply splicing adhesive to the pig ear and the wall. Allow to dry, until tacky to the touch and then press the pig ear tight to the wall. Roll tightly with two inch wide steel roller. Seal all exposed edges and fold with Lap Sealant.

Outside Corners: Apply a uniform coat of Tape Primer to the curb flashing and onto the deck membrane where the outside corner is to be installed. Prior to placement of the outside corner, peel off the blue poly film and fold in half lengthwise. Peel off one side of the clear release liner. Press the folded flashing tightly into the angle change and press firmly against the vertical surface. Place the folded flashing tightly into the angle change. Starting at the lowest point on the corner press and mold the flashing out onto the horizontal (deck) surface. Roll tightly with two inch wide steel roller. Seal all exposed edges and fold with Lap Sealant.

CAUTIONS AND WARNINGS

A heat gun may be required for forming outside corners in colder temperatures. Job site storage temperatures in excess of 90°F (32°C) may affect the shelf life of the product.

Form # PDS-E-6
Date 01/01/2007

MULE-HIDE PRODUCTS CO., INC.

P.O. Box 1057, Beloit, WI 53512-1057 • 608/365-3111 • Fax: 608/365-7852

PRODUCT DATA SHEET

MULE-HIDE PRE-CUT INSIDE/OUTSIDE CORNERS

TECHNICAL SERVICES

Contact Mule-Hide Products Co., Inc. at 608/365-3111 for additional information.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not make nor does it authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Mule-Hide's physical properties. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury of person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the complaint or failure before repairs are made.

Form # PDS-E-6
Date 01/01/2007

MULE-HIDE PRODUCTS CO., INC.

P.O. Box 1057, Beloit, WI 53512-1057 • 608/365-3111 • Fax: 608/365-7852

PRODUCT DATA SHEET

MULE-HIDE PRODUCTS CO., INC.

P.O. Box 1057, Beloit, WI 53512-1057 • 608/365-3111 • Fax: 608/365-7852