

PRODUCT DATA SHEET

MULE-HIDE PVC NON-REINFORCED FLASHING

PRODUCT DESCRIPTION

Mule-Hide PVC Non-Reinforced Flashing is a non-reinforced thermoplastic poly vinyl chloride based membrane.

BASIC USES

Mule-Hide PVC Non-Reinforced Flashing is used for sealing joints of Mule-Hide PVC Coated Metal, drain details and field flashing pipes and other details where reinforced membrane or the used of pre-molded accessories are not feasible.

SPECIFICATIONS

Color: White, Gray
Material: Non-reinforced PVC based membrane
Sizes: 12"x 50' (30cm x 15m)
24"x 50' (60cm x 15m)

TYPICAL PHYSICAL PROPERTIES

Property	Test Method	Specification
Tolerance on nominal Thickness, %	ASTM D 751	+/- 08
Tensile Strength MD (psi. min.) TD	ASTM D 638	1500
Elongation MD (%, min.) TD	ASTM D 638	250/200
Weight, lb/ft ² (kg/m ²), typical		.51 lb/ft ²
Tear strength, min., lbf/in (kN/m)	ASTM D 1004	10
Heat aging: 28 days % Retention	ASTM D 4434	90
Resistance to Xenon-arc weathering Xenon-arc, 5040 kJ/m ² total Radiant exposure, visual Condition at 7X	ASTM D 4434	No cracking/crazing Negligible discoloration

STORAGE

Mule-Hide PVC Flashing Membrane should be kept clean and dry prior to installation.

INSTALLATION INSTRUCTIONS

Refer to Mule-Hide Details published in the Mule-Hide PVC Specifications Manual.

PRECAUTIONS

Do not install Mule-Hide PVC Flashing in direct contact with asphalt or coal tar pitch. The Mule-Hide PVC Flashing is to be installed with the white/gray side up, dark gray side down - **Do not reverse.**

Form # PDS-PVC02
Date 01/01/2007

MULE-HIDE PRODUCTS CO., INC.

P.O. Box 1057, Beloit, WI 53512-1057 • 608/365-3111 • Fax: 608/365-7852

MULE-HIDE PVC NON-REINFORCED FLASHING (Page 2)

TECHNICAL SERVICES

Contact Mule-Hide Products Co., Inc. at 608/365-3111 for customer service to obtain additional information.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not make nor does it authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Mule-Hide's physical properties. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury of person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the complaint or failure before repairs are made.

Form # PDS-PVC-02
Date 01/01/2007

MULE-HIDE PRODUCTS CO., INC.

P.O. Box 1057, Beloit, WI 53512-1057 • 608/365-3111 • Fax: 608/365-7852