

MULE-HIDE SA-MB WATER BASE VERTICAL PRIMER

PRODUCT DESCRIPTION

Mule-Hide SA-MB Water Base Vertical Primer is an acrylic latex-based adhesive with superior bonding performance. The product is green in color when dry. The solids content is approximately 51%, and the overall texture is similar to latex paint.

BASIC USES: FOR VERTICAL APPLICATION ONLY!

This product is designed as a primer to be used on approved vertical substrates prior to the application of the self-adhering Mule-Hide SA-Base Sheet or the self-adhering Mule-Hide SA-SBS or SA-APP Cap Sheets.

PRODUCT BENEFITS

- Non-flammable and non-toxic
- Once set, will not break down when immersed in water for prolonged periods of time.
- Application temperature performance is satisfactory above 45° F and below 165° F.
- Installs easily and smoothly, which speeds up operations.
- Can be re-sealed in container without set taking place.
- Available in 3.5 gallon pails and 5 gallon pails.

Note: For Vertical Application Only.

COVERAGE

The coverage rate is approximately 200 - 300 square feet per gallon (at 4 - 6 wet mils). Porous surfaces such as concrete block may require additional product.

APPLICATION

Can be sprayed, rolled or brushed on almost any acceptable vertical substrate. Stir thoroughly prior to use.

DO NOT THIN!

INSTALLATION TEMPERATURE

Do not use adhesive if ambient temperature is below 45°F or if night time temperatures are expected to fall below 40°F within 48 hours after application.

CAUTION: Product must be stored above 60° F. The product cannot be used once frozen. Do not let Mule-Hide SA MB Water Base Vertical Primer freeze. It is difficult to clean up when spilled on unrelated surfaces if left to dry. Do not double-stack pallets. (See MSDS for more information).

INSTALLATION

Surfaces must be clean and free of grease, dirt, oil, water and other contaminants before applying primer. If surface is contaminated, clean prior to primer application to insure proper adhesion. Using a short or medium nap roller or commercial spray equipment, apply a uniform coat (approximately 4 – 6 wet mils) of primer to the substrate and allow to dry to the point it is tacky to the touch. The primer will turn green as it dries.

Do not install the membrane over wet primer. Drying time at ambient temperatures is about 20 - 30 minutes. Cooler temperatures and high humidity will extend drying time.

Form # PDS-MB08
Date 6/30/05

MULE-HIDE PRODUCTS CO., INC.

P.O. Box 1057, Beloit, WI 53512-1057 • 608/365-3111 • Fax: 608/365-7852

MULE-HIDE SA-MB WATER BASE VERTICAL PRIMER

The self adhering modified bitumen membrane can then be applied to the dry primed surface as per the manufacturers directions. Intimate contact of the self adhered membrane and primer must be made with a stiff broom or roller after membrane application. Follow Mule-Hide's guidelines for termination, mechanical attachment and/or flashing of the self adhering membrane, using good roofing practice.

CLEAN UP

The adhesive can be removed from hands when wet with water and a light detergent. When dry, use a solvent followed by soap and water.

With spray equipment, use water followed by solvent cleaners, followed by water with detergent. Paint roller covers can be left in material until next usage or cleaned with water when wet.

Material spillage can be removed easily with water when wet. If adhesive has dried, peel off as much surface adhesive as possible and clean area with solvent until removed.

HANDLING

Mule-Hide maintains Material Safety Data Sheets on all of its products. Material Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. Mule-Hide's Material Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Mule-Hide products in your facilities.

RECOMMENDED STORAGE

Store in unopened original containers at 60° F - 80° F for maximum storage life. Higher temperatures reduce normal storage life. **DO NOT ALLOW TO FREEZE.** Rotate stock.

CUSTOMER SERVICE

Contact Mule-Hide Products Company at 608/365-3111 for product information.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not make nor does it authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Mule-Hide's physical properties. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury of person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the complaint or failure before repairs are made.

Form # PDS-MB08
Date 6/30/05

MULE-HIDE PRODUCTS CO., INC.

P.O. Box 1057, Beloit, WI 53512-1057 • 608/365-3111 • Fax: 608/365-7852