

**SEAL-FAST ALUMINUM TAPE**

**DESCRIPTION**

Mule-Hide Seal-Fast<sup>®</sup> Aluminum Tape is a non-butyl synthetic rubber and resin adhesive tape that is bonded to a thick, 4-mil aluminum metal backing. The adhesive coating is protected by a thin, siliconized release liner, which is removed prior to application.

**BASIC USES**

Seal-Fast<sup>®</sup> Aluminum Tape may be used on metal buildings, trailer/RV roofs and sides, drain pans, drain pipes, ductwork, boats, canoes, and as a protective coating for surfaces where abrasion and corrosion resistance is required. The Seal-Fast<sup>®</sup> Aluminum Tape seals to itself so that it can be cut and folded around an object.

**PHYSICAL DATA**

Application Temp	Above -10°F (-23°C)
Total Thickness	20 mils (0.51 mm)
Adhesion	>17 lbs/in width (to unprimed aluminum)
Flexibility	Excellent
Tensile Strength	>1000 psi
Weathering	Excellent resistance to wind, rain, erosion and ultra violet rays.
Shelf Life	Up to 5 years

**SURFACE PREPARATION**

Surface must be clean and dry. Moisture, dust, dirt, or other foreign matter should be removed. Remove oil and grease, etc. with a suitable cleaner. Remove salt and other contaminants.

**PACKAGING**

Packaged in cartons:

2" x 50' (12 per ctn)

4" x 50' (6 per ctn)

6" x 50' (4 per ctn)

**APPLICATION**

Cut tape to desired lengths and shapes. Remove the release liner to expose the adhesive coating. Press tape firmly to surface to obtain conformability and adhesion. Apply pressure aggressively by using a steel roller. When applied to surfaces which permit spiral wrapping, allow for one-half inch overlap to insure seal. Installation to temperatures as low as -10°F is possible by treating the surface with Seal-Fast<sup>®</sup> Primer prior to installation and maintaining Seal-Fast<sup>®</sup> Aluminum Tape at roof temperature (+60 °F) before applying.

**TECHNICAL SERVICE**

Contact Mule-Hide Products Company at (608) 365-1111 for technical service information.

**DISCLAIMER**

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not make nor does it authorize anyone to make any warranty of merchantability or fitness for any purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Mule-Hide's physical properties. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury of person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the complaint or failure before repairs are made.

**MULE-HIDE PRODUCTS CO., INC.**

P.O. Box 1057, Beloit, WI 53512-1057 • 608/365-3-111 • Fax: 608/365-7852

[www.mulehide.com](http://www.mulehide.com)

Form # SealTapeAlum  
Revised April 2009