

SEAL-FAST® DOUBLE-STICK TAPE

PRODUCT DESCRIPTION

Mule-Hide Seal-Fast® Double-Stick Tape is a non-butyl synthetic rubber and resin adhesive tape, which remains flexible even in cold temperatures. This product is supplied with double facers and is designed to bond two surfaces creating a water-tight, conformable seal.

BASIC USES

Mule-Hide Seal-Fast® Double-Stick Tape adheres to a wide variety of substrates including EPDM, TPO, most PVC, CSPE/Hypalon, CPE, SBS & APP Modified, asphalt BUR, coat tar BUR, tiles, coated and non-coated aluminum and metal roofs. Also adheres to galvanized steel, gypsum board, wood, polyethylene, propylene, rigid polystyrene, rigid fiberglass, brick, concrete, masonry, OSB board, etc.

Used to create a water-tight, conformable seal or weather proof bond between two surfaces. Use as a lap seal, under the foot of an equipment curb or skylight. Can be rolled into a bead or ball to form a gasket, seal a gap or seal, as needed.

SPECIFICATIONS

Comprised of 100% solids consisting of synthetic resins, thermoplastics and non-curing rubber (non-butyl) with a built-in primer, sandwiched between two silicone release liners.

TYPICAL PHYSICAL PROPERTIES

Description	Value
Adhesion	19 lbs / in. width
Application Temperature	150°F to -20°F ambient
Dielectric Strength	Exceeds 12 kV
Elongation	>500%
Low temperature flexibility	½" radius at -30°F
Permanence	.001 perms maximum
Pliability	No cracks in membrane
Shelf Life	Up to 5 years
Temperature flexibility range	-70°F - > 200°F

PACKAGING

Packaged in cartons: 1" x 50' (24 rolls per carton)
2" x 50' (12 rolls per carton)

SURFACE PREPARATION

Surface must be clean and dry. Moisture, dust, dirt, or other foreign matter should be removed. Remove, oil, grease, and other contaminants with Seal-Fast Cleaner or a non-residue cleaner such as acetone or lacquer thinner.

May be applied to clean, dry surfaces from 150°F to -20°F ambient.

For applications below 40°F ambient (and above -20°F), treat surfaces with Seal-Fast Primer

SEAL-FAST[®] DOUBLE-STICK TAPE

APPLICATION

To bond two materials together.

Remove one side of the release liner and apply to the surface to be protected or bonded. Roll firmly with a steel hand roller to activate the bonding process. Remove the second release liner and apply second surface to tape. Roll firmly to activate the bonding process.

To use as a putty.

Remove both release liners and roll double-stick tape into a rope. Place over gap and mold to seal opening.

PROTECTION & SAFETY

Mule-Hide maintains Material Safety Data Sheets on all of its products. Material Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. Mule-Hide's Material Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Mule-Hide products in your facilities.

ADDITIONAL INFORMATION

The information given on this PDS is subject to change without notice. Always check the Mule-Hide website at www.mulehide.com for the latest information, changes and updates or contact Mule-Hide Products Company at 800-786-1492.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. This product may be eligible for a Mule-Hide warranty, please check the Mule-Hide website at www.mulehide.com or contact Mule-Hide directly at 800-786-1492 for details. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made.