

PRODUCT DATA SHEET

SEAL-FAST® PRIMER

DESCRIPTION

Mule-Hide Seal-Fast® Primer is a solvent based primer specifically formulated to prime surfaces to be bonded with Seal-Fast® Tape or Seal-Fast® Fabric Tape in temperatures below 40°F.

BASIC USES

Mule-Hide Seal-Fast® Primer is used to ensure proper adhesion when installing Seal-Fast® Tape or Seal-Fast® Fabric Tape in temperature below 40°F or when the surface quality is questionable. Seal-Fast® Primer is also used on mortar, porous surfaces and granulated surfaces*. **Do not use on PVC membranes.**

PHYSICAL DATA

Flash Point	109°F (TAG CC)
Boiling Point	282°F initial
Solubility in Water	29 ppm @ 73°F
% Volatile by Volume	80-90
Specific Gravity	1.3

COLOR

Light Brown

PACKAGING

12 quarts per ctn

APPLICATION

Use Seal-Fast® Primer when surface temperature falls below 40°F or when surface quality is questionable. **Step 1:** All surfaces should be thoroughly cleaned and dry prior to applying the Seal-Fast® Primer. **Step 2:** Stir or shake well before using. **Step 3:** Brush thin coat over surface. Do not allow product to pool. *On granulated surfaces, granules must be removed prior to applying primer. **Do not thin Seal-Fast® Primer.** **Step 4:** Allow Seal-Fast® Primer to dry completely before applying Seal-Fast® Tapes. One quart will cover approximately 75 sq. ft. depending on surface porosity and method of application. **Note: Do not apply Seal-Fast® Primer to PVC based materials.**

TECHNICAL SERVICE

Contact Mule-Hide Products Company at (608) 365-3111 for technical service information.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not make nor does it authorize anyone to make any warranty of merchantability or fitness for any purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Mule-Hide's physical properties. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury of person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the complaint or failure before repairs are made.

Form # PDS SealPrimer
Date 08/2004

MULE-HIDE PRODUCTS CO., INC.

P.O. Box 1057, Beloit, WI 53512-1057 • 608/365-3111 • Fax: 608/365-7852