

SHUR-GARD ACRYLIC WATER BASE BONDING ADHESIVE**PRODUCT DESCRIPTION**

Shur-Gard "Acrylic Water Base Bonding Adhesive" (WBA) is an acrylic latex-based adhesive with superior bonding performance. The product is white in color when wet and is clear when dry. The solids content is approximately 60%, and the overall texture is similar to latex paint.

BASIC USES: FOR HORIZONTAL APPLICATION ONLY!

Single Side Adhesive: Can only be used as a single-side adhesive when applying over porous surfaces such as plywood, OSB, Dens-Deck, wood, high density fiberboard, moisture-resistant drywall. Single-side application is when the adhesive is only applied to one surface (normally the substrate), and the sheet is immediately rolled in place into the white, wet adhesive. When applied as a single-side adhesive, the EPDM membrane may be moved and adjusted to remove any wrinkles. Working time before set-up takes place is approximately 15 to 20 minutes. As this product is water based and contains no solvents, actual drying time is dependent on temperature and humidity.

Contact Adhesive: Can be used as a contact adhesive over non-porous or porous surfaces. This application requires the adhesive to be put on both surfaces to be adhered: then the adhesive is left to dry before mating the surfaces. Can be used on metal, concrete or certain sealed horizontal surfaces. It may also be used as a contact adhesive on approved foam insulations with acceptable facers.

PRODUCT BENEFITS

- Non-flammable and non-toxic
- Once set, will not break down when immersed in water for prolonged periods of time.
- Application temperature performance is satisfactory above 45° F and below 165° F.
- Installs easily and smoothly, which speeds up operations.
- Can be re-sealed in container without set taking place.
- Available in 1 gallon pails, 5 gallon pails and 55 gallon drums.

Note: For Horizontal Application Only. The Maximum Permissible Slope is 2" per foot.

COVERAGE

The estimated (theoretical) coverage rates at room temperature are:

- Porous surfaces, 100 to 120 square feet per gallon (1 side application)
- Non-porous surfaces, 50 to 60 square feet per gallon (2 side application)

RECOMMENDED STORAGE

Store in unopened original containers at 60° F - 80° F for maximum storage life. Higher temperatures reduce normal storage life. **DO NOT ALLOW TO FREEZE.** Rotate stock.

APPLICATION

Can be sprayed, rolled or brushed on almost any acceptable substrate.

Date: 1/2007

MULE-HIDE PRODUCTS CO., INC.

P.O. Box 1057, Beloit, WI 53512-1057 • 608/365-3111 • Fax: 608/365-7852

SHUR-GARD ACRYLIC WATER BASE BONDING ADHESIVE

INSTALLATION TEMPERATURE

Do not use adhesive if ambient temperature is below 45°F or if night time temperatures are expected to fall below 40°F within 48 hours after application.

CAUTION: Product must be stored above 60° F. The product cannot be used once frozen. Do not let Shur-Gard Water Base Bonding Adhesive freeze. It is difficult to clean up when spilled on unrelated surfaces if left to dry. Do not double-stack pallets. (See MSDS for more information).

CLEAN UP

The adhesive can be removed from hands when wet with water and a light detergent. When dry, use a solvent followed by soap and water. With spray equipment, use water followed by solvent cleaners, followed by water with detergent. Paint roller covers can be left in material until next usage or cleaned with water when wet. Material spillage can be removed easily with water when wet. If adhesive has dried, peel off as much surface adhesive as possible and clean area with solvent until removed.

INSTALLATION OVER A POROUS SURFACE

Once the EPDM membrane has been positioned and given sufficient time to relax, fold the membrane in half exposing the substrate (deck) surface to be adhered. Starting at the fold, apply adhesive to substrate (deck) only. As you proceed with the adhesive, bring the membrane into the wet, white adhesive. We recommend laying the membrane into the adhesive as soon as possible. This ensures the wetting of the EPDM surface. Once half of the sheet is in place, use a push broom to sweep the surface, keeping a steady pressure with the broom against the surface of the sheet, mating surfaces and eliminating captured air between the membrane and substrate (deck). If any wrinkles are present, re-position the sheet by using a push broom or by hand to remove the wrinkle. Repeat the procedure for the second half of the sheet.

NOTE: Traffic over membrane should be held to a minimum. You will note footprints in the sheet as the set takes place if you walk across the sheet. These prints should be broomed out and will be less visible once the adhesive cures.

INSTALLATION OVER A NON-POROUS SURFACE

Position the EPDM membrane and fold the membrane in half, exposing the substrate (deck) surface to be adhered to. Starting at the fold, apply adhesive not only to the substrate (deck) but also to the back side of the exposed membrane. First apply adhesive on the membrane, then on the substrate.

When both surfaces are dry, the surface will be clear with no white or wet adhesive showing. Gently roll the membrane back into place, taking precaution not to capture air between the substrate and the sheet. Once the sheet is in place, use a push broom to assure mating of the surfaces. Should a wrinkle appear that cannot be worked out with your hand or broom, slowly peel back the membrane, re-position the membrane and put it back in place. This should only be attempted immediately after setting the membrane and may require both surfaces to be re-glued. Using a push broom with pressure, sweep the troubled area assuring mating of the surfaces. Repeat the procedure for the second half of the sheet.

HANDLING

Mule-Hide maintains Material Safety Data Sheets on all of its products. Material Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. Mule-Hide's Material Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Mule-Hide products in your facilities.

Date: 1/2007

MULE-HIDE PRODUCTS CO., INC.

P.O. Box 1057, Beloit, WI 53512-1057 • 608/365-3111 • Fax: 608/365-7852

SHUR-GARD ACRYLIC WATER BASE BONDING ADHESIVE

TECHNICAL SERVICE

Contact Mule-Hide Products Company at 608/365-3111 for additional information.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not make nor does it authorize anyone to make any warranty of merchantability or fitness for any purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Mule-Hide's physical properties. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury of person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the complaint or failure before repairs are made.