

MULE-HIDE TAPE PRIMER

PRODUCT DESCRIPTION

Mule-Hide Tape Primer is a solvent-based cleaner specifically formulated to clean and prime EPDM and TPO membrane surfaces to be bonded with In-Seam Tapes, Uncured Flashing Tapes and Cured Cover Tapes. Mule-Hide Tape Primer is required to prepare EPDM and TPO membrane surfaces prior to the application of Mule-Hide Tapes and Lap Sealants.

PRODUCT BENEFITS

Ensures excellent adhesion with Tape Products and Splice Adhesives.

PACKAGING AND STORAGE

DOT Label Required: Flammable Liquid

When Mule-Hide Tape Primer is stored in its original, unopened container, indoors and out of direct sunlight at temperatures below 80°F, the shelf life is 12 months. Always rotate stock.

INSTALLATION INSTRUCTIONS

Thoroughly clean both mating surfaces with Mule-Hide Tape Primer and Scotch-Brite® pads or clean rags. When seaming Black EPDM membranes, both surfaces to be mated must be solid black in color with no streaking. When seaming White-on-Black EPDM membranes, both surfaces should exhibit a uniform blue hue appearance without streaking. When using Mule-Hide Uncured Flashing and Cured Cover Tapes, the Tapes may be applied as soon as the cleaner has dried (but tacky to the touch). The area primed should be wider than the actual surfaces to be bonded to ensure bonding only to primed surfaces. If pads or rags become filled with talc (mica dust) or dirt, discard and replace with new.

PRECAUTIONS

Mule-Hide Tape Primer contains ingredients that could be harmful if mishandled. Contact with skin and eyes should be avoided and necessary protective equipment and clothing should be worn. Mule-Hide maintains Material Safety Data Sheets on all of its products. Material Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. Mule-Hide's Material Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Mule-Hide products in your facilities.

TECHNICAL SERVICES

Contact Mule-Hide Products Co., Inc. at 608/365-3111 for additional information.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not make nor does it authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Mule-Hide's physical properties. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury of person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the complaint or failure before repairs are made.

Form # PDS-E-16
Date 01/01/2007

MULE-HIDE PRODUCTS CO., INC.

P.O. Box 1057, Beloit, WI 53512-1057 • 608/365-3111 • Fax: 608/365-7852