

MULE-HIDE UNCURED EPDM FLASHING TAPE - WHITE

PRODUCT DESCRIPTION

Mule-Hide Uncured EPDM Flashing Tape is an uncured EPDM flashing membrane laminated to cured butyl rubber tape and rolled onto a release liner.

BASIC USES

Mule-Hide Uncured EPDM Flashing Tape was specifically developed for use with EPDM single-ply membrane roofing systems. Mule-Hide's flashing tapes may be used in conjunction with the Mule-Hide Tape Primer to flash inside and outside corners, pipes, pitch pockets or other penetrations that require the flashing to be molded or conform to an irregular shape. Mule-Hide's Uncured EPDM Flashing Tapes are **not permitted** for use in flashing gravel stops, drip aprons or stripping seams or batten bars.

SPECIFICATIONS

Base Polymer	Membrane -EPDM Adhesive -Synthetic Rubber
Color	WHITE
Ozone Resistance 100 pphm Ozone in air 168 hours @ 104°F @ 50% strain	No cracks
Nominal Thickness	95 mil (1.91 mm)
Brittleness Temperature	-49°F
Nominal Width 9" 12"	Membrane 9" (230 mm) -Adhesive 9-3/16" (235 mm) Membrane 12" (305 mm) -Adhesive 12-3/16" (310 mm)

Typical Values: Based on material tested in our laboratories but variable from sample to sample. Typical values should not be construed as a guaranteed analysis of any specific lot or as specification items.

PACKAGING

Width	Length	Unit	Weight
9"	50 lf.	1 per case	16.5 pounds
12"	50 lf.	1 per case	22 pounds

BENEFITS & SUPPLEMENTAL STATEMENTS

- Contains no solvent
- Labor savings up to 50%
- Superior tack and green strength
- Superior peel and shear strengths
- Ease of installation
- Reduces application problems of adhesives
- Strength improves with age

INSTALLATION

Using Scotch-Brite® scrub pads or clean rags, clean the membrane area thoroughly with Mule-Hide's Tape Primer. Unroll the flashing tape and cut a sufficient amount to flash the detail. Install the Mule-Hide Uncured EPDM Flashing Tape in accordance with the appropriate current printed Mule-Hide specification and details.

MULE-HIDE UNCURED EPDM FLASHING TAPE - WHITE

STORAGE & HANDLING

Mule-Hide Uncured EPDM Flashing Tape is a combination of both cured and uncured product. For this reason Mule-Hide recommends the shelf life not exceed 9 months. Stock should be rotated.

PROTECTION & SAFETY

1. Avoid prolonged contact with skin. In case of contact with skin, thoroughly wash affected area with soap and water.
2. Prolonged job site storage temperatures in excess of 90°F (32°C) may affect product shelf life. In warm, sunny weather; keep Product rolls in their box or in a shaded area until ready to use.
3. Storage and use of Product at temperatures below 40°F (4°C) will result in a loss of adhesive tack, and in extreme cases, will result in no bond to the substrate. Overnight storage must be available to keep the temperature of the Product at a minimum of 60°F (15°C). Hot boxes for job site storage must be provided to maintain a minimum product temperature of 40°F (4°C).
4. Product must be stored in a dry area.
5. Due to solvent flash-off, condensation may form on applied Primer when the ambient temperature is near the dew point. If condensation develops, the application of Primer and Product must be discontinued since proper adhesion will not be achieved. Allow the surface to dry and apply Primer to the previously coated surface and apply Product when conditions allow.
6. Do not allow waste products (petroleum, grease, oil, solvents, vegetable or mineral oil, animal fats, etc.) or direct steam venting to come in contact with the Sure-White Product.
7. A heat gun is required when forming Product in colder temperatures as outlined in the specification.
8. KEEP OUT OF THE REACH OF CHILDREN.

Mule-Hide maintains Material Safety Data Sheets on all of its products. Material Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. Mule-Hide's Material Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Mule-Hide products in your facilities.

ADDITIONAL INFORMATION

The information given on this PDS is subject to change without notice. Always check the Mule-Hide website at www.mulehide.com for the latest information, changes and updates or contact Mule-Hide Products Company at 800-786-1492.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. This product may be eligible for a Mule-Hide warranty, please check the Mule-Hide website at www.mulehide.com or contact Mule-Hide directly at 800-786-1492 for details. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made.