

**MULE-HIDE WATER CUT-OFF**

**PRODUCT DESCRIPTION**

Mule-Hide Water Cut-Off is a butyl-based, one-component mastic designed specifically for sealing Mule-Hide membranes to wood, concrete, metal, plastic and other substrates.

**BASIC USES**

Mule-Hide Water Cut-Off can be used to seal roofing membranes to stop water penetration into the roofing system. Common uses are at drain terminations and behind Mule-Hide's All Purpose Bars at wall terminations.

**PRODUCT BENEFITS**

- High solids content
- Solvent will not attack polystyrene foam insulation
- Remains flexible

**SPECIFICATIONS**

Typical Liquid Properties\* at 77°F

Base Polymer	Butyl
Total Solids, %	80%
Viscosity, cps	800,000 - 1,800,000 cps
Brookfield	
Specific Gravity	1.20 - 1.32
Net weight per gallon	10.00 - 11.20 lbs.
Color	Grey
Solvents	Mineral Spirits
Flash Point	40°F(4°C) Closed Cup

\*Typical Values: Based on material tested in our laboratories but variable from sample to sample. Typical values should not be construed as a guaranteed analysis of any specific lot or as specification items.

Coverage at 77°F, (theoretical) 200 Linear ft/gal - 20 linear ft/cartridge

**PACKAGING AND STORAGE**

**DOT Label Required:** Yellow

10 (11 OZ) Cartridges per carton

Mule-Hide Water Cut-Off should be stored in unopened cartridges between 60°F and 80°F for no longer than 1 year. Rotate stock regularly.

**INSTALLATION INSTRUCTIONS**

Extrude a bead of Mule-Hide Water Cut-Off onto the substrate at the termination point of the Mule-Hide membrane. The membrane must cover the mastic. Follow Mule-Hide's Specification Manual and Details for appropriate methods of termination.

Form # PDS-E-20

Revised: Nov 2008

**MULE-HIDE PRODUCTS CO., INC.**

P.O. Box 1057, Beloit, WI 53512-1057 • 608/365-3111 • Fax: 608/365-7852

www.mulehide.com

**MULE-HIDE WATER CUT-OFF**

**PRECAUTIONS**

Mule-Hide Water Cut-Off mastic contains ingredients which could be harmful if mishandled. Contact with skin and eyes should be avoided and necessary protective equipment and clothing should be worn.

Mule-Hide maintains Material Safety Data Sheets on all of its products. Material Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. Mule-Hide's Material Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Mule-Hide products in your facilities.

**TECHNICAL SERVICES**

Contact Mule-Hide Products Co., Inc. at 608/365-3111 for additional information.

**DISCLAIMER**

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not make nor does it authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Mule-Hide's physical properties. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury of person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the complaint or failure before repairs are made.

Form # PDS-E-20  
Revised: Nov 2008

**MULE-HIDE PRODUCTS CO., INC.**

P.O. Box 1057, Beloit, WI 53512-1057 • 608/365-3111 • Fax: 608/365-7852  
www.mulehide.com